

Pending claims:

Claims 1-18 are cancelled.

19. (Currently Amended) A product for providing a configuration database subsystem that maintains configuration data for objects in a network for a router device comprising:

instructions for directing a processing unit in said router device to:

maintain a configuration database,

receive a notification request sent from one of a plurality of subsystems in said router device, wherein said notification request is a request to receive notification of changes to configuration data of an object in said network identified in said notification request and wherein each of said plurality of subsystems is instructions executed by said processing unit to provide an application of an internetwork operating system;~~;~~ and

store an identification of said one of said plurality of subsystems that transmitted said notification request in a record in said database that stores said configuration data for said object identified in said notification request wherein said identification identifies said one of said plurality of subsystems as a subsystem to notify in response to a change in said configuration data for said object in said record;~~;~~

set a notification flag in said record wherein said notification flag indicates that a notification must be sent responsive to a change,

receive a change in said configuration data of said object,
retrieve said record of said object,
read said notification flag,
determining whether said notification flag is set,
read said identification of said one of said plurality of subsystems
from said record of said object receiving to receiving said change of said
configuration data responsive to a determination that said notification flag is set,
and
transmit a notification of said change of configuration data of said
object to said one of said plurality of subsystems responsive to said reading of said
identification; and
 a media readable by said processing unit that stores said instructions.

Claims 20-22 (Cancelled)

23. (Currently Amended) The product of claim ~~24~~ 19 wherein said instructions further comprise:

instructions for directing said processing unit to:

determine said notification request is configuration data of a name space,

retrieve each child record of said record, and

set a notification flag in each said child record.

24. (Previously Presented) The product of said 23 wherein said instructions further comprise:

instructions for directing said processing unit to:

receive a change to configuration in a child record,

retrieve said child record responsive to receiving said change,

read said notification flag in said child record responsive to retrieving said record,

read a parent record of said child responsive to reading said notification flag, and

transmit notification of said change of said change to said one of said plurality of subsystems identified in said parent record.

25. (Previously Presented) The product of claim 19 wherein said instructions further comprise:

instructions for directing said processing unit to:

receive a remove notification request from said one of said plurality of subsystems, wherein said remove notification request is a request to remove said one of said plurality of subsystems from said plurality of subsystems to be notified in response to a change in said configuration data, and

remove said identification of said one of said plurality of subsystems from said record of said configuration data storing subsystems to be notified of a change in said configuration data.

26. (Previously Presented) The product of claim 25 wherein said instructions further comprise:

instructions for directing said processing unit to:

determine whether said configuration data for which said remove notification request is for a name space,

retrieve each child record of said record of said configuration data responsive to a determination said configuration data is a name space, and

remove a notification flag from each said child record.

27. (Currently Amended) A method for providing a configuration database subsystem that maintains configuration data for objects in a network for a router device comprising:

maintaining a configuration database;

receiving a notification request sent from one of a plurality of subsystems in said router device, wherein said notification request is a request to receive notification of changes to configuration data of an object in said network identified in said notification request and wherein each of said plurality of subsystems is instructions executed by said processing unit to provide an application of an internetwork operating system;

storing an identification of said one of said plurality of subsystems that transmitted said notification request in a record in said database that stores said configuration data for said object identified in said notification request wherein

said identification identifies said one of said plurality of subsystems as a subsystem to notify in response to a change in said configuration data for said object in said record; ~~and~~

setting a notification flag in said record wherein said notification flag indicates that notification is required responsive to a change;

receiving a change in said configuration data of said object;

retrieving said record of said object;

reading said notification flag;

determining whether said notification flag is set;

reading said identification of said one of said plurality of subsystems from said record of said object receiving to receiving said change of said configuration data responsive to a determination that said notification flag is set; and

transmitting a notification of said change of configuration data of said object to said one of said plurality of subsystems responsive to said reading of said identification.

Claims 28-30 (Cancelled)

31. (Currently Amended) The method of claim ~~29~~ 27 further comprising:

determining said notification request is configuration data of a name space;

retrieving each child record of said record; and

setting a notification flag in each said child record.

32. (Previously Presented) The method of claim 31 further comprising:
- receiving a change to configuration in a child record;
 - retrieving said child record responsive to receiving said change;
 - reading said notification flag in said child record responsive to retrieving said record;
 - reading a parent record of said child responsive to reading said notification flag; and
 - transmitting notification of said change of said change to said one of said plurality of subsystems identified in said parent record.
33. (Previously Presented) The method of claim 27 further comprising:
- receiving a remove notification request from said one of said plurality of subsystems, wherein said remove notification request is a request to remove said one of said plurality of subsystems from said plurality of subsystems to be notified in response to a change in said configuration data; and
 - removing said identification of said one of said plurality of subsystems from said record of said configuration data storing subsystems to be notified of a change in said configuration data.
34. (Previously Presented) The method of claim 33 further comprising:
- determining whether said configuration data for which said remove notification request is for a name space;

retrieving each child record of said record of said configuration data
responsive to a determination said configuration data is a name space; and
removing a notification flag from each said child record.